

Product	P3 indoor full color LED module
Module size	192*192mm
Pixel density	111111dots/m²
LED lamp	SMD2121
Module resolution	64*64
Module consumption	30W/pcs
Viewing distance	3-25m
Max power consumption	850W/m²
Standard cabinet size	576*576mm
Drive mode	1/32scan
Brightness	≥1200cd/m²
HUB mode	HUB75
Drive IC	FM5020
Frame frequency	≧60Hz/s
Refresh rate	≧360Hz/s
MTTF	>5000 hours
Life time	>100,000 hours

Defect rate	<0.0001	
Video signal input	RF, S-video, RGB, RGBHV, YUV, YC, composition	
Temperature range	Storage	-20 to 65°C
	Working	-20 to 50°C
Gray scale/color	4096 grades for R ,G and B	
Display	≥16.7M colors	
Working voltage	110/220V AC	
Viewing angle	Horizontal	140°
	Vertical	140°
Display content	videos, pictures and graphics	
Operating humidity	10-90%	
Storage humidity	10-90%	
Continue working time	24 hours	
Control mode	synchronization/asynchronization	
Warranty	2 years	
Module weight	0.28KG/PCS	
Delivery time	7-15 days	

The module is made of automatic filling machine to ensure uniform, smooth and waterproof.

Anti-corrosion, anti-aging, anti-corona, high temperature and other characteristics.

The box is made of aluminum-magnesium-zinc alloy custom-made die-cast aluminum box, which is not easy to be deformed, corrosion resistant, heat dissipation, prolong product life, thin design, easy transportation and installation.

Stainless steel lock connection, more solid, stable, safe;

Die-cast aluminum one-time compression molding, high precision, seamless splicing;

Professional aviation plug, beautiful and stable, low loss;

Can be customized dual backup power to prevent the sudden situation;

Can be customized air distribution cabinet, easy to use

